

Designed for possibilities. Made for people.

NEW AND IMPROVED

Enhancements focused on the road ahead

Altro bus floors have been re-engineered for up to 20% weight savings, but it doesn't end there. We've also introduced a Heavy Duty Plus variant and added a range of other benefits to make the industry's first-choice safety flooring even better.

- Lighter
- Stronger
- Enhanced durability
- Naturally hygienic
- Even better to install

Build quality from the ground up with the lightest 2.7mm safety floor.

The next step in safety flooring

Altro Transflor ChromaTM

Typical applications:


Bus, coach, shuttle, emergency vehicles, recreational, specialty vehicles, mobility vehicles, mobile medical units, mobile food, delivery trucks, utility vehicles, people movers, and non-restricted rail.

Newly enhanced, this chip design bus floor is now up to 20% lighter. Further enhanced with increased strength and durability it is engineered for excellent slip resistance, design flexibility and heavy duty performance.


Stronger, more durable and up to 20% lighter, the all new Altro Transflor Chroma offers the perfect balance of performance and design. Offering sustained slip resistance to the most comprehensive range of industry standards, Altro Transflor Chroma mitigates slip risks to one in a million for uncompromised safety. Available in a wide range of colors and two versatile thicknesses - 2.7mm Heavy Duty Plus and 2.2mm Heavy Duty - Altro Transflor Chroma is engineered to meet the most challenging public transport demands.

Why not streamline your installation by using our kit cutting service or self-adhesive options?


lightweight safety flooring for the transportation industry



Strada TFCR2263 (2.2 mm) TFCR2763 (2.7 mm) WR81 / AM81 / LRV 26



Cayman TFCR2261 (2.2 mm) TFCR2761 (2.7 mm) WR83 / AM83 / LRV 14




Mineral TFCR2230 (2.2 mm) TFCR2730 (2.7 mm) WR83 / AM83 / LRV 16




Tuscan TFCR2278 (2.2 mm) TFCR2778 (2.7 mm) WR83 / AM83 / LRV 14



Sprint TFCR2274 (2.2 mm) TFCR2774 (2.7 mm) WR248 / AM238 / LRV 12



Viper TFCR2265 (2.2 mm) TFCR2765 (2.7 mm) WR83 / AM83 / LRV14




Cyber TFCR2202 (2.2 mm) TFCR2702 (2.7 mm) WR83 / AM83 / LRV 14




Gene TFCR2203 (2.2 mm) TFCR2703 (2.7 mm) WR72 / AM72 / LRV 8




Forester TFCR22904 (2.2 mm) TFCR27904 (2.7 mm) WR474 / AM308 / LRV 12




Sigma TFCR2282 (2.2 mm) TFCR2782 (2.7 mm) WR83 / AM83 / 14



TFCR2233 (2.2 mm) TFCR2733 (2.7 mm) WR83 / AM83 / LRV 15



Patriot TFCR22908 (2.2 mm) TFCR27908 (2.7 mm) WR101 / AM72 / LRV 10



Quattro TFCR2275 (2.2 mm) TFCR2775 (2.7 mm) WR249 / AM249 / LRV 15



Lancer TFCR22914 (2.2 mm) TFCR27914 (2.7 mm) WR102 / AM200 / LRV 9



Capri TFCR2260 (2.2 mm) TFCR2760 (2.7 mm) WR231 / AM73 / LRV 11




Phantom TFCR2272 (2.2 mm) TFCR2772 (2.7 mm) WR100 / AM00 / LRV 7

AM = Mastic



Frontier TFCR22905 (2.2 mm) TFCR27905 (2.7 mm) WR62 / AM62 LRV 10



Acadia TFCR22001 (2.2 mm) TFCR27001 (2.7 mm) WR83 / AM83 LRV 14

Accent and safety colors



Safety Yellow LRV:46 TFM2229 (2.2 mm) TFM2729 (2.7 mm) WR08 / AM200



Safety White LRV: 58 TFM2200 (2.2 mm) TFM2700 (2.7 mm) WR01 / AM01

Dimensions	6'7" x 65'7" / 2 m x 20 m	
Thickness	2.2 mm	2.7 mm
Weight	4.05 lb/yd ²	4.98 lb/yd2
Format	ROLL and KIT	

















transflor@altro.com









Color matched Weldrods (WR) and Mastics (AM) are available. You'll find their product codes under product SKUs.

LRV = Light Reflectance Value



Samples Experience has shown that printing cannot reproduce colors accurately.

All products available in roll and

kit format. Custom colors are also

If color choice is critical please request a sample of the material.

available.